

Rectangle Small Hollow

Overview

CLOUDFORM COLLECTION



Specifications

| | | | |
|--------------------------|---|----------------------------|--|
| LIGHTING | Integrated LED light source offering high lumen output and efficacy. Color consistency of 3 SDCM. See additional information summarizing lumen distribution, wattage, and efficacy on following pages. Tunable white option available. | DRIVERS | 120–277V constant current, dimming driver standard. Can be wired dimming or non-dimming. 0–10v dimming input with a range of 1%–100%. Dim-to-Off standard. Driver can be accessed from the fixture. Power factor of > .95. Total Harmonic Distortion (THD) of < 20%. |
| LUMEN MAINTENANCE | Reported TM-21 Lifetimes L90(17k) = 52,600 hours L80(17k) > 102,000 hours L70(17k) > 102,000 hours | CERTIFICATION | Luminaire is CSA listed conforming to UL Standard 1598 in the U.S. and CAN/CSA C22.2 No. 250.0 in Canada. In accordance with NEC Code 410.73 (G), this luminaire contains an internal driver disconnect. Damp Location Rated. All electronic components are RoHS compliant, and the mechanical components of the luminaire have been verified to meet RoHS Directive 2002/95/EC. |
| CONSTRUCTION | 1/16" 3form Varia. White Opal top and bottom diffuser. Contact your local sales rep for material samples. | CLEANING & CARE | Designed to withstand the demands of rigorous cleaning requirements. Effective cleaning and disinfection of environmental surfaces reduces microbe transmission. Superior chemical resistance and durability promotes safety in any design application. Use common disinfectants and cleaners to reduce microbe transmission. |
| ELECTRICAL | Emergency battery output: 6 watts for 90 minutes. Maximum Mounting height: 10.5ft. Compatible with Signify Bodine sinusoidal output emergency lighting inverters. Signify Bodine inverters allow designated lighting fixtures to serve as code compliant emergency lighting sources during failure of normal AC power. For additional information see link: http://www.bodine.com/products/inverter.html | WARRANTY | 5 year warranty on all standard components. |
| MOUNTING | Adjustable stainless steel aircraft cable, contact studio for lengths over 20'. Available with multiple drop height J-hooks for group frame. Available with Grid hook for T-Grid Frame. | | |




Rectangle Small Hollow

Fixture Options

CLOUDFORM COLLECTION

DIMENSIONS



46"L x 70"W x 4"D

46"L x 70"W x 8"D

VARIA COLORS OPTIONS



CAULDRON
N41



ALMOND
N20



GYPSUM
N06



JARDIN
G59



CITYSCAPE
N45



MOONSTONE
N31



POME-
GRANATE
R37



REDWOOD
N31



GINGER
R14



SQUASH
Y14



VAPOR
W05



EARL GREY
TEAK



TOFFEE
CHESTNUT



VANILLA
ASH



HONEY OAT



DARK
MOCHA
WALNUT



BROWN
SUGAR
WALNUT



BOURBON
CHERRY




Rectangle Small Hollow


CLOUDFORM COLLECTION

CEILING CONNECTIONS

CABLES TO CEILING




4" OCTAGONAL JUNCTION BOX (BY OTHERS)



CANOPY/DRESS PLATE FINISH OPTIONS




DECK MOUNT



GRID MOUNT

Contact LightArt for Grid Mount hook options




Rectangle Small Hollow

Lighting Details

CLOUDFORM COLLECTION

LIGHT DISTRIBUTION OPTIONS

Consult factory or lightart.com for IES files, tested in accordance with IESNA LM79



PERFORMANCE – RECTANGLE SMALL HOLLOW
Based on 3500K / 90CRI / Standard Distribution

| NOMINAL LUMEN OUTPUT (LM/FT) | INPUT POWER (W/FT) | EFFICACY (LM/W) |
|------------------------------|--------------------|-----------------|
| 4324 | 43 | 100 |
| 6050 | 61 | 98 |
| 7788 | 80 | 97 |
| 9516 | 100 | 95 |
| 11244 | 120 | 94 |
| 12970 | 141 | 92 |
| 14708 | 163 | 90 |
| 16436 | 185 | 89 |
| 18164 | 209 | 87 |
| 19888 | 233 | 85 |

LIGHT DISTRIBUTION
Based on measurement data

| COLOR TEMPERATURE / CRI | MULTIPLIER |
|-------------------------|------------|
| 2700K / 80 | 0.98 |
| 2700K / 90 | 0.93 |
| 3000K / 80 | 1.02 |
| 3000K / 90 | 0.97 |
| 3500K / 80 | 1.00 |
| 3500K / 90 | 1.00 |
| 4000K / 80 | 1.08 |
| 4000K / 90 | 1.03 |

OUTPUT MULTIPLIERS INSTRUCTIONS

Adjusted Value = $L_1 \times C_m$ where:
 L_1 = (Lumen output at 3500K / 90 CRI) ×
 C_m = (Color Temp. / CRI Multiplier) ×
Example:
850LM / 3000K / 80CRI
(850) × (1.02) = 789LM

Rectangle Small Hollow

Part Number
Specification

CLOUDFORM COLLECTION

SPECIFICATION CODE

Example: 2 QTY CLF-LIGHT-SREC-4H-GIN-DM-STD-830CK-550LM-P01-WPC-WH

QTY.

CLF-LIGHT-SREC-

1

2

3

4

5

6

7

8

9

Complete form to order Cloudform Rectangle Small Hollow fixture(s). For each number, make one selection and enter in the corresponding box above.
*Indicates modified choices; additional lead times and/or costs may apply.

1

HEIGHT

4H

4" HEIGHT

8H

8" HEIGHT

2

MATERIAL

CAU

CHALDRON

MOO

MOONSTONE

JAR

JARDIN

CIT

CITYSCAPE

GYP

GYPSUM

POM

RED

GIN

GINGER

SQU

SQUASH

ALM

ALMOND

VAP

VAPOR

POMEGRANATE

REDWOOD

GINGER

SQUASH

ALMOND

VAPOR

ESW

BROWN SUGAR WALNUT

TCH

TOFFEE CHESTNUT

VAN

VANILLA ASH

OAT

HONEY OAT

DMW

DARK MOCHA WALNUT

EGT

EARL GREY TEAK

BRC

BOURBON CHERRY

3

MOUNTING

DM

DECK MOUNT

GFM

GROUP FRAME MOUNT

TGRD

T-GRID MOUNT

4

SUSPENSION

STD

12" – 96"

EXT

12" – 240"

5

LED CRI / CCT

827CK

80 CRI / 2700K

830CK

80 CRI / 3000K

835CK

80 CRI / 3500K

840CK

80 CRI / 4000K

927CK

90 CRI / 2700K

930CK

90 CRI / 3000K

935CK

90 CRI / 3500K

940CK

90 CRI / 4000K

TW

TUNABLE WHITE

6

OUTPUT

250LM

250 LM/FT

350LM

350 LM/FT

450LM

450 LM/FT

550LM

550 LM/FT

650LM

650 LM/FT

750LM

750 LM/FT

850LM

850 LM/FT *Max Tunable White*

950LM

950 LM/FT *Max EM Battery Option*

1050LM

1050 LM/FT

1150LM

1150 LM/FT

CU*

CUSTOM OUTPUT

lm

CONTINUE TO NEXT PAGE TO COMPLETE SPECIFICATION

align

Declare.

Red List Free
Ingredients

MADE IN USA
WITH GLOBAL AND
DOMESTIC PRODUCTS

LightArt

206.524.2223 LIGHTART.COM
4770 OHIO AVE S STE B, SEATTLE, WA 98134

RECTANGLE SMALL HOLLOW
07/29/25 UPDATE 5/6

Rectangle Small Hollow

Part Number
Specification

CLOUDFORM COLLECTION

CONTINUE SPECIFICATION

7 DIMMING AND CONTROLS

- ☐ P01
- ☐ LEC*
- ☐ EBM
- ☐ DALI
- 0-10V 1% DIMMING
- HI-LUME 1% ECOSYSTEM LED DRIVER SOFT ON, FADE TO BLACK (LDE1 SERIES)
- 0-10V 1% DIMMING INTEGRATED EM BATTERY OPTION
*Max Lumen output limited—consult LightArt.
Not available with Tunable White.*
- DALI CONTROL

8 CANOPY OPTIONS

- ☐ WPC
- ☐ BPC
- WHITE
- BLACK

9 POWER CORD

- ☐ WH
- ☐ BK
- WHITE
- BLACK

*Indicates modified choices; additional lead times and/or costs may apply.

