



Specifications


LIGHTING	Integrated LED light source offering high lumen output and efficacy. Color consistency of 3 SDCM. See additional information summarizing lumen distribution, wattage, and efficacy on following pages. Tunable white option available.	DRIVERS	120–277V constant current, dimming driver standard. Can be wired dimming or non-dimming. 0–10v dimming input with a range of 1%–100%. Dim-to-Off standard. Driver can be accessed from the fixture for higher lumen outputs. Driver accessible at canopy for lower lumen output. Power factor of > .95. Total Harmonic Distortion (THD) of < 20%.
LUMEN MAINTENANCE	Reported TM-21 Lifetimes L90(17k) = 52,600 hours L80(17k) > 102,000 hours L70(17k) > 102,000 hours	CERTIFICATION	Luminaire is CSA listed conforming to UL Standard 1598 in the U.S. and CAN/CSA C22.2 No. 250.0 in Canada. In accordance with NEC Code 410.73 (G), this luminaire contains an internal driver disconnect. Damp Location Rated. All electronic components are RoHS compliant, and the mechanical components of the luminaire have been verified to meet RoHS Directive 2002/95/EC.
CONSTRUCTION	1/16" 3form Varia. White Opal top and bottom diffuser. Contact your local sales rep for material samples.	CLEANING & CARE	Designed to withstand the demands of rigorous cleaning requirements. Effective cleaning and disinfection of environmental surfaces reduces microbe transmission. Superior chemical resistance and durability promotes safety in any design application. Use common disinfectants and cleaners to reduce microbe transmission.
ELECTRICAL	Emergency battery output: 6 watts for 90 minutes. Maximum Mounting height: 16ft. Compatible with Signify Bodine sinusoidal output emergency lighting inverters. Signify Bodine inverters allow designated lighting fixtures to serve as code compliant emergency lighting sources during failure of normal AC power. For additional information see link: http://www.bodine.com/products/inverter.html	WARRANTY	5 year warranty on all standard components.
MOUNTING	Adjustable stainless steel aircraft cable, contact studio for lengths over 20'. Available with multiple drop height J-hooks for group frame. Available with Grid hook for T-Grid Frame.		



Hexagon Solid

CLOUDFORM COLLECTION

DIMENSIONS



VARIA COLORS OPTIONS




Hexagon Solid


CLOUDFORM COLLECTION

CEILING CONNECTIONS

CABLES TO CEILING




ULTRA SHALLOW CANOPY



CK 19000+ lumens, TW 10000+ lumens, EM all lumens, available only with Ultra Shallow Canopy.


4" OCTAGONAL JUNCTION BOX (BY OTHERS)



CANOPY / DRESS PLATE FINISH OPTIONS



DECK MOUNT



THREADED ROD
(Provided by Installer)

ESCUTCHEON PLATE


CABLE SWAGE

THREADED CONNECTOR

STAINLESS STEEL CABLE


GRID MOUNT

Contact LightArt for Grid Mount hook options



For CK, not available for 19000+ lumens.
For EM, not available.
For TW, not available for 10000+ lumens

GRIP HOOK




Hexagon Solid

Lighting Details


CLOUDFORM COLLECTION

LIGHT DISTRIBUTION OPTIONS

Consult factory or lightart.com for IES files, tested in accordance with IESNA LM79



SIDE VIEW



TOP VIEW

PERFORMANCE – HEXAGON SOLID

Based on 3500K / 90CRI / Standard Distribution

NOMINAL LUMEN OUTPUT (LM)	INPUT POWER (W)	EFFICACY (LM/W)
995	9	108
1989	19	107
2984	28	107
3978	37	107
4973	47	106
5967	57	105
6962	66	105
7956	76	104
8951	86	104
9945	96	104
10940	106	103
11934	116	103
12929	127	102
13923	137	101
14918	147	101
15913	158	101
16907	169	100
17902	179	100
18896	191	99
19891	202	98

LIGHT DISTRIBUTION

Based on measurement data

COLOR TEMPERATURE / CRI	MULTIPLIER
2700K / 80	0.98
2700K / 90	0.93
3000K / 80	1.02
3000K / 90	0.97
3500K / 80	1.00
3500K / 90	1.00
4000K / 80	1.08
4000K / 90	1.03

OUTPUT MULTIPLIERS INSTRUCTIONS

Adjusted Value = $L_1 \times C_m$ where:

L_1 = (Lumen output at 3500K / 90 CRI) ×

C_m = (Color Temp. / CRI Multiplier) ×

Example:

850LM / 3000K / 80CRI

$(850) \times (1.02) = 789\text{LM}$

Hexagon Solid

Part Number Specification

CLOUDFORM COLLECTION

SPECIFICATION CODE

Example: 2 QTY CLF-LIGHT-SHEX-4H-GIN-DM-STD-930CK-5000LM-P01-WPC-WH

QTY.

CLF-LIGHT-SHEX

1

2

3

4

5

6

7

8

9

Complete form to order Cloudform Hexagon Solid fixture(s). For each number, make one selection and enter in the corresponding box above.
*Indicates modified choices; additional lead times and/or costs may apply.

1 HEIGHT

4H

4" HEIGHT

8H

8" HEIGHT

2 MATERIAL

CAU

MOO

JAR

CIT

GYP

CHALDRON

MOONSTONE

JARDIN

CITYSCAPE

GYPSUM

POM

RED

GIN

SQU

ALM

VAP

POMEGRANATE

REDWOOD

GINGER

SQUASH

ALMOND

VAPOR

ESW

TCH

VAN

OAT

DMW

EGT

BRC

BROWN SUGAR WALNUT

TOFFEE CHESTNUT

VANILLA ASH

HONEY OAT

DARK MOCHA WALNUT

EARL GREY TEAK

BOURBON CHERRY

3 MOUNTING

4 SUSPENSION

DM

DECK MOUNT

GFM

GROUP FRAME MOUNT

TGRD

T-GRID MOUNT

STD

12" – 96"

EXT

12" – 240"

5 LED CRI / CCT

827CK

80 CRI / 2700K

830CK

80 CRI / 3000K

835CK

80 CRI / 3500K

840CK

80 CRI / 4000K

927CK

90 CRI / 2700K

930CK

90 CRI / 3000K

935CK

90 CRI / 3500K

940CK

90 CRI / 4000K

TW

TUNABLE WHITE

CONTINUE TO NEXT PAGE TO COMPLETE SPECIFICATION

CONTINUE SPECIFICATION

6 OUTPUT

<input type="checkbox"/> 1000LM	1000 LM	<input type="checkbox"/> 12000LM	12000 LM
<input type="checkbox"/> 2000LM	2000 LM	<input type="checkbox"/> 13000LM	13000 LM
<input type="checkbox"/> 3000LM	3000 LM	<input type="checkbox"/> 14000LM	14000 LM
<input type="checkbox"/> 4000LM	4000 LM	<input type="checkbox"/> 15000LM	15000 LM
<input type="checkbox"/> 5000LM	5000 LM	<input type="checkbox"/> 16000LM	16000 LM
<input type="checkbox"/> 6000LM	6000 LM	<input type="checkbox"/> 17000LM	17000 LM <i>Max Tunable White</i>
<input type="checkbox"/> 7000LM	7000 LM	<input type="checkbox"/> 18000LM	18000 LM <i>Max EM Battery Option</i>
<input type="checkbox"/> 8000LM	8000 LM	<input type="checkbox"/> 19000LM	19000 LM
<input type="checkbox"/> 9000LM	9000 LM	<input type="checkbox"/> 20000LM	20000 LM
<input type="checkbox"/> 10000LM	10000 LM	<input type="checkbox"/> CU*	CUSTOM OUTPUT
<input type="checkbox"/> 11000LM	11000LM		

lm

7 DIMMING AND CONTROLS

<input type="checkbox"/> P01	0-10V 1% DIMMING
<input type="checkbox"/> LEC*	HI-LUME 1% ECOSYSTEM LED DRIVER SOFT ON, FADE TO BLACK (LDE1 SERIES)
<input type="checkbox"/> EBM	0-10V 1% DIMMING INTEGRATED EM BATTERY OPTION <i>Max Lumen output limited—consult LightArt. Not available with Tunable White.</i>
<input type="checkbox"/> DALI	DALI CONTROL

8 CANOPY OPTIONS

<input type="checkbox"/> WPC	WHITE
<input type="checkbox"/> BPC	BLACK

9 POWER CORD

<input type="checkbox"/> WH	WHITE
<input type="checkbox"/> BK	BLACK

*Indicates modified choices; additional lead times and/or costs may apply.