

Specifications

1/32" thick 3form Varia resin. SHADE White Opal top and bottom diffuser.

LIGHTING Solid state LED system

120v-277v input 2700K - 4000K 80/90 CRI light source Small 25w / 1301 lumens Medium 40w / 2722 lumens 50w / 4174 lumens Large X-Large 71w / 5626 lumens

LUMEN MAINTENANCE Reported TM-21 Lifetimes

L90(17k) = 52,600 hoursL80(17k) > 102,000 hours L90(17k) > 102,000 hours

HARDWARE Removable TGIC-free powder coated metal lid.

Canopy and dress plate mounts to standard junction box (junction box provided by others).

3/64" stainless steel cables to ceiling. Power cord to canopy

Dimming 0-10v DIMMING

MOUNTING Fully adjustable stainless steel aircraft cable.

Contact LightArt for lengths over 20'.

CERTIFICATION CSA approved to UL standards

Declare label certified

Living Building Challenge compliant

Damp rated

WARRANTY 5 year warranty on all standard components.

LED system rated for operation in ambient

environments up to 25°C.

STANDARDS 6 week lead time

250+ 3 form material options

(contact LightArt for custom material pricing)

TGIC-free powder coat PVC-free power cord











Slim Rings

DIMENSIONS











CEILING CONNECTIONS

OFFSET JUNCTION BOX







RECESSED* For recessed canopy, cut 11" dia hole and recess j-box or mounting structure by 1.5"

4" OCTAGONAL JUNCTION BOX (BY OTHERS)



Required for powered units: optional for unlit units

CANOPY/DRESS PLATE FINISH OPTIONS





WHITE

COLOR OPTIONS



Due to manufacturing and construction process used to create the Essentials and $\,$ Connected collection, Pattern+ and wood grains will not match at fixture seams. Lead times subject to change.







Slim Rings

	LA2-SI	LIM-RING -	2 2 QTY LA2-SL	IM-RING-43D-WZ-	830CK-STD-WPC-	wн 6		
Complete form to order Slim Ring(s). For each number, make one selection and enter in the corresponding box above. *Indicates modified choices; additional lead times and/or costs may apply.								
SIZE 2 MATERIAL								
	21.5D 33D 43D 57.5D	21.5" DIA 33" DIA 43" DIA 57.5" DIA		GO NL CR SO CB2 VC WZ CUST*	GESSO NATURAL CINDER SILKEN OYSTE CRANBERRY ×2 VITAMIN C WIZARD CUSTOM COLO	2		
•	LED CRI/CCT				• CHODENICION			
3 !	827CK 830CK 835CK 840CK 927CK	80 CRI / 2700K 80 CRI / 3000K 80 CRI / 3500K 80 CRI / 4000K 90 CRI / 2700K	930СК 935СК	90 CRI / 3000K 90 CRI / 3500K	_ 4	SUSPENSION STD EXT*	12" – 96" 24" – 240"	_
5	CANOPY OPTIC	CABLES TO CEILING CABLES TO CANOPY*	6 CANOPY WP BP0	C WHITE	0	POWER CORD	WHITE BLACK	

*Indicates modified choices; additional lead times and/or costs may apply.





