

Specifications

LIGHTING Solid state LED system. 120v-277v input; 2700K-4000K in CRI >80 or 90; 8W

HARDWARE TGIC-free powder coated backplate mounts to

standard junction box (provided by others) Canopy and dress plate mounts to standard

DIMMING Dimming 0-10v CERTIFICATION CSA approved to UL standards

Damp rated. ADA Compliant.

WARRANTY 5 year warranty on all standard components.

LED system rated for operation in ambient

environments up to 25°C.

STANDARDS 6 week lead time

250+ 3form material options TGIC-free powder coat PVC-free power cord











SHAPES & DIMENSIONS

0 12"W×8"H×4"D

SHADE COLOR OPTIONS



Due to manufacturing and construction process used to create the Essentials and Connected collection, Pattern+ and wood grains will not match at fixture seams. Lead times subject to change.

CANOPY / DRESS PLATE FINISH OPTIONS

WHITE









ECO Part Number Specification

SPECIFICATION CODE Example: 2 QTY COL-ECO-SCN-8H-LIK-830CK-WPB					
QT		ECO-SCN -	0 0	3 4	
Complete form to order Zero fixture(s). For each number, make one selection and enter in the corresponding box above. *Indicates modified choices; additional lead times and/or costs may apply.					
SIZE SIZE MATERIAL					
[8H	8"H	LIN	LINEA IVORY + NOIR	
			LIK	LINEA IVORY + KHAKI	
			LI	LINEA IVORY	
			☐ VP	VEIL PURE	
			TS	TRANSLUCENT SUEDE	
			CUST*	CUSTOM COLOR	
3 LED CRI/CCT 4 BACKPLATE COLOR					
,					
l	827CK	80 CRI / 2700K	930CK	90 CRI / 3000K WHITE	
l	830CK	80 CRI / 3000K	935CK	90 CRI / 3500K	
l	835CK	80 CRI / 3500K			
l					
	927CK	90 CRI / 2700K			
[840CK	80 CRI / 3500K 80 CRI / 4000K 90 CRI / 2700K			

*Indicates modified choices; additional lead times and/or costs may apply.









