## Four Overview



### Specifications

1/16" thick 3form Varia resin. White Opal top and **SHADES** 

bottom diffuser.

LIGHTING Solid State LED system

120v-277v input;

3000k

80 CRI light source Small 6.4w Medium 14.8w 22.2w Large XLarge 29.6w

**LUMEN MAINTENANCE** Calculated: Reported:

L90: >55,000 hours L70: >180,000 hours

L80: >120,000 hours EPA TM21 calculator derived

**PHOTOMETRICS** Consult factory or website for IES files,

tested in accordance with IESNA LM79.

**HARDWARE** Stainless steel backplate mounts to standard junction

box in wall (provied by others).

DIMMING Dimming 0-10v

MOUNTING Fully adjustable stainless steel aircraft cable, contact

studio for lengths over to 20'.

WARRANTY 5 year warranty on all standard components. LED

system rated for operation in ambient environments up

to 25°C.

CERTIFICATION CSA approved to UL standards

Declare label certified

Living Building Challenge compliant

Damp rated

**STANDARDS** 6 week lead

250+ 3form material options.

(Contact for custom material pricing.)

TGIC-free powder coat PVC-free power cord












**AVAILABLE SIZES** All modules are 48" in Width and 4" in Depth



#### VARIA COLORS OPTIONS



#### BACK PLATE FINISH OPTIONS



STAINLESS STEEL









# Four Part Number Specification

SPECIFICATION CODE Example: 2 QTY LA2 - ESS - FOUR - 45D - GO - STD								5CK-WL-SSE	3					
[ c	LA2-E	ESS-FOUR	-		3	4	<b>5</b>	6						
*Ind	Complete form to order LA2 Essentials Four fixture(s). For each number, make one selection and enter in the corresponding box above.  *Indicates modified choices; additional lead times and/or costs may apply.  DIAMETER / FIN CONFIGURATION All modules are 5"W x 4"D  MATERIAL													
	12H 24H 36H 48H	12" HEIGHT 24" HEIGHT 36" HEIGHT 48" HEIGHT			_ •	GC NL CR SO CB	2	GESSO NATURA CINDER SILKEN CRANBE	L [	VC WZ MCR CUST	w M	ITAMIN C /IZARD IIDCENTURY ROSE\ USTOM COLOR	WOOD	
	STD EXT	12" – 96" 12" – 240"						827CK 830CK 835CK 840CK	80 CRI / 2700K 80 CRI / 3000K 80 CRI / 3500K 80 CRI / 4000K	9270 930 9350 940	CK 9	90 CRI / 2700K 90 CRI / 3000K 90 CRI / 3500K 90 CRI / 4000K		
<b>6</b>	MOUNTING OPTIONS  WL WL WALL MOUNT CL CEILING MOUNT						6 BA	BACKPLATE COLOR  SSB STAINLESS STEEL						
6	☐ WL	WL WALL MOUNT					6 <u>BA</u>	_		TEEL	_			





