



Specifications

LIGHTING	Integrated LED light source offering high lumen output and efficacy. Color consistency of 3 SDCM. See additional information summarizing lumen distribution, wattage, and efficacy on following pages. Tunable white and RGB options available.	CERTIFICATION	Luminaire is CSA listed conforming to UL Standard 1598 in the U.S. and CAN/CSA C22.2 No. 250.0 in Canada. In accordance with NEC Code 410.73 (G), this luminaire contains an internal driver disconnect. Damp Location Rated. All electronic components are RoHS compliant, and the mechanical components of the luminaire have been verified to meet RoHS Directive 2002/95/EC.
LUMEN MAINTENANCE	Reported TM-21 Lifetimes L90(17k) = 52,600 hours L80(17k) > 102,000 hours L70(17k) > 102,000 hours	SHADES	4.5mm thick Sola Felt, a PET material manufactured with 50% post-consumer recycled content. Sola Felt is a LBC Red List Free labeled product, eligible for LEED, Living Building Challenge, and other green building certification credits.
CONSTRUCTION	1/16" 3form Varia. White Opal top and bottom diffuser. Contact your local sales rep for material samples.	CLEANING & CARE	The best way to remove airborne debris and dust from shades is to periodically vacuum. A Swiffer sheet or feathered duster can also be used for light dusting. To treat liquid stains, remove spills immediately with a clean damp cotton cloth or with detergent soap and warm water. Carpet and fabric cleaners can usually be used. Always test an inconspicuous area before applying cleaners to the actual stain
ELECTRICAL	Emergency battery output: 6 watts for 90 minutes. Maximum Mounting height: 10.5ft. Compatible with Signify Bodine sinusoidal output emergency lighting inverters. Signify Bodine inverters allow designated lighting fixtures to serve as code compliant emergency lighting sources during failure of normal AC power. For additional information see link: http://www.bodine.com/products/inverter.html	WARRANTY	5 year warranty on all standard components.
MOUNTING	Adjustable stainless steel aircraft cable, contact studio for lengths over 20'		
DRIVERS	120-277V constant current, dimming driver standard. Can be wired dimming or non-dimming. 0-10v dimming input with a range of 1%-100%. Dim-to-Off standard. Driver can be accessed from the fixture. Power factor of > .95. Total Harmonic Distortion (THD) of < 20%.		




Acoustic Box

Fixture Options


ACOUSTIC COLLECTION

DIMENSIONS


24" SQUARE



32" SQUARE



48" SQUARE





CEILING CONNECTIONS

24" SQUARE | 32" SQUARE


12" canopy standard for 24" Square and 32" Square

48" SQUARE

The 12" canopy is provided for configurations using standard LEDs from 1000-12000 lumens without an EM Battery, and for fixtures using Tunable White LEDs with a lumen range of 1-6000 lumens. All other configurations will use a driver box on board the fixture with a 6" Ultra Shallow Canopy.



4" OCTAGONAL JUNCTION BOX (BY OTHERS)



Required for powered units;
optional for unlit units

CANOPY/DRESS PLATE FINISH OPTIONS



Acoustic Box

Lighting Details

ACOUSTIC COLLECTION

PERFORMANCE – ACOUSTIC BOX 24"
Based on 3500K / 90CRI / Standard Distribution

NOMINAL LUMEN OUTPUT (LM)	INPUT POWER (W)	EFFICACY (LM/W)
1018	11.79	86.30
2016	24.11	83.60
2995	36.96	81.00
3979	50.38	79.00
4973	64.58	77.00
5971	79.45	75.20
6970	95.12	73.30
7958	111.77	71.20
8972	129.20	69.40

PERFORMANCE – ACOUSTIC BOX 32"
Based on 3500K / 90CRI / Standard Distribution

NOMINAL LUMEN OUTPUT (LM)	INPUT POWER (W)	EFFICACY (LM/W)
1038	11.88	87.40
2001	24	83.40
3021	36.43	82.90
4031	49.09	82.10
5022	62.03	81.00
6013	75.31	79.80
6986	88.88	78.60
8006	102.70	78.00
8958	116.91	76.60
9960	131.56	75.70
10940	146.54	74.70
11970	161.99	73.90

PERFORMANCE – ACOUSTIC BOX 48"
Based on 3500K / 90CRI / Standard Distribution

NOMINAL LUMEN OUTPUT (LM)	INPUT POWER (W)	EFFICACY (LM/W)
968	12.75	75.90
2060	25.56	80.60
3010	38.35	78.50
4084	51.52	79.30
5034	64.81	77.70
6108	78.30	78.00
7040	91.87	76.60
8096	105.69	76.60
9012	119.36	75.50
10050	133.48	75.30
10982	147.84	74.30
12004	162.32	74.00
13024	177.05	73.60
14028	191.64	73.20
14924	206.67	72.20
15928	221.88	71.80
16932	237.42	71.30
17916	253.13	70.80
18884	268.96	70.20
19976	284.90	70.10

LIGHT DISTRIBUTION
Based on measurement data

COLOR TEMPERATURE / CRI	MULTIPLIER
2700K / 80	0.98
2700K / 90	0.93
3000K / 80	1.02
3000K / 90	0.97
3500K / 80	1.00
3500K / 90	1.00
4000K / 80	1.08
4000K / 90	1.03

OUTPUT MULTIPLIERS INSTRUCTIONS

Adjusted Value = $L_1 \times C_m$ where:
 L_1 = (Lumen output at 3500K / 90 CRI) ×
 C_m = (Color Temp. / CRI Multiplier) ×
Example:
850LM / 3000K / 80CRI
(850) × (1.02) = 789LM



SABINS PER FIXTURE Equivalent square feet of perfect absorption

CENTER FREQUENCY (HZ)	48SQ 24H BOX	44SQ 48H BOX
100	29.47	35.38
125	24.69	35.78
160	20.34	36.15
200	22.00	38.94
250	25.15	43.99
315	26.36	45.07
400	27.24	47.58
500	26.77	45.83
630	24.72	47.38
800	26.47	49.52
1000	27.24	49.08
1250	26.73	50.62
1600	27.08	52.15
2000	28.17	52.88
2500	28.93	53.83
3150	28.31	54.76
4000	29.82	56.29
5000	29.71	56.69
AVERAGE OF 250, 500, 1000, 2000	26.41	48.07
EQUIVALENT SQ FT OF ACT (NRC 0.90)	29.30	53.40
EQUIVALENT SQ FT OF ACT (NRC 0.70)	37.70	68.70


Absorption

NRC per Fixture: 0.85–1.00
Average of values taken at
250, 500, 1000, and 2000 Hz

The NRC of felt depends on its configuration.
LightArt fixtures utilize deep airspaces and
multiple layers to keep NRC ratings high for all
exposed felt surfaces.

The acoustic testing of Acoustic Box was
conducted at NVLAP accredited laboratories
and meets ISO 354 and ASTM C423. Formal test
reports are available upon request.

- 48SQ 48H BOX
- 48SQ 24H BOX



Acoustic Box

Part Number Specification

ACOUSTIC COLLECTION

SPECIFICATION CODE

Example: 2 QTY ACC-BOX-32SQ-24H-SLT-STD-927CK-6000LM-P01-RWPC-WH-CCN

ACC-SHPE-BOX-

-

-

-

-

-

-

-

-

-

-

-

QTY.

1

2

3

4

5

6

7

8

9

10

Complete form to order Acoustic Drum fixture(s). For each number, make one selection and enter in the corresponding box above.
*Indicates modified choices; additional lead times and/or costs may apply.

1

SIZE

Nominal

24SQ

24" SQUARE

32SQ

32" SQUARE

48SQ

48" SQUARE

2

HEIGHT

Nominal

12H

12" HEIGHT

24H

24" HEIGHT

36H

36" HEIGHT48H

3

FELT COLOR

COLOR OPTIONS

EB

EBONY

NF

NIGHTFALL

CA

CAST

SLT

SILTMLSTLARNIZN

EM

EMERALD

BU

BURGUNDYCIJPSFOCHMUASCT

LC

LILAC

AD

ADMIRALDKSTBPTDWDNVL

COLOR OPTIONS

DWA

WALNUT

IOK

IRON OAK

WA

CARMEL OAKBA

4

SUSPENSION

STD

12" – 96"

EXT*

24" – 240"

5

LED CRI/CCT

827CK

80 CRI / 2700K

830CK

80 CRI / 3000K

835CK

80 CRI / 3500K840CK927CK

930CK

90 CRI / 3000K

935CK

90 CRI / 3500K940CKTW

CONTINUE TO NEXT PAGE TO COMPLETE SPECIFICATION

Acoustic Box

Part Number Specification

ACOUSTIC COLLECTION

CONTINUE SPECIFICATION

6 OUTPUT

☐ 1000LM	1000 LM	☐ 12000LM	12000 LM 32"SQ Max SO 48"SQ Max TW and EM Batt
☐ 2000LM	2000 LM	☐ 13000LM	13000 LM
☐ 3000LM	3000 LM	☐ 14000LM	14000 LM
☐ 4000LM	4000 LM	☐ 15000LM	15000 LM
☐ 5000LM	5000 LM	☐ 16000LM	16000 LM
☐ 6000LM	6000 LM 24"-32" SQ Max Tunable White and EM Battery Option	☐ 17000LM	17000 LM
☐ 7000LM	7000 LM	☐ 18000LM	18000 LM
☐ 8000LM	8000 LM	☐ 1900LM	19000 LM
☐ 9000LM	9000 LM 24"SQ Max Standard Output	☐ 20000LM	20000 LM 48"SQ Max Standard Output
☐ 10000LM	10000 LM	☐ CU*	CUSTOM OUTPUT
☐ 11000LM	11000 LM		

lm

7 DIMMING AND CONTROLS

☐ P01	0-10V 1% DIMMING
☐ LEC*	HI-LUME 1% ECOSYSTEM LED DRIVER SOFT ON, FADE TO BLACK (LDE1 SERIES)
☐ EBM	0-10V 1% DIMMING INTEGRATED EM BATTERY OPTION Max Lumen output limited—consult LightArt. Not available with Tunable White.
☐ DALI	DALI CONTROL

8 CANOPY OPTIONS

☐ WPC	WHITE
☐ BPC	BLACK
☐ RWPC	RECESSED WHITE
☐ RBPC	RECESSED BLACK

9 POWER CORD

☐ WH	WHITE
☐ BK	BLACK

10 CABLE CONNECTION

☐ CCL	CABLES TO CEILING
☐ CCN	CABLES TO CANOPY Only Available on 24" Square—consult LightArt for larger sizes.

*Indicates modified choices; additional lead times and/or costs may apply.



LightArt

206.524.2223 LIGHTART.COM
4770 OHIO AVE S STE B, SEATTLE, WA 98134

ACOUSTIC BOX
11/24/25 UPDATE 7/7