

Specifications

CONSTRUCTION 1/16" 3from Varia. White Opal top and bottom diffuser

Contact your local sales rep for material samples.

LIGHTING Solid state LED system. 120v-277v input; 2700K-4000K in CRI >80 or CRI >90. Dimming 0-10v; Small 42W / LED

Lumens 2917; Medium 82W / LED Lumens 152; Large 152W

Consult factory or website for IES files, tested in **PHOTOMETRICS**

accordance with IESNA LM79

HARDWARE TGIC-free powder coated canopy. Canopy and dress

plate mounts to standard junction box (junction box provided by others). Sureface mount option available Stainless steel cable with nickel-plated cable gripper allows for adjustable hanging height. Made with RoHS

compliant parts.

MOUNTING Fully adjustable stainless steel aircraft cable.

CERTIFICATION CSA approved to UL standards. Declare certification.

WARRANTY 5 year warranty on all standard components.

LED system rated for operation in ambient

temperatures up to 25°C.

Suitable for Dry or Damp locations.

Indoor use only.

LEAD TIME 6 week lead time **CLEANING & CARE**

Designed to with the demands of rigorous cleaning requirements. Effective cleaning and disinfection of enviromental surfaces reduces microbe transmission. Superior chemical resistance and durability promotes safety in any design application. Use common disinfectants and cleaners to reduce microbe transmission.









Fixture Options LA2 ESSENTIALS

DIMENSIONS HEIGHT, WIDTH, LENGTH 4"H 8"H 12"H 22"SQ 22"SQ 22"SQ 4"H 8"H 12"H 30"SQ 30"SQ 30"SQ 4"H 8"H 48"SQ 48"SQ 12"H 48"SQ



FELT COLOR OPTIONS




CANOPY/DRESS PLATE FINISH OPTIONS



CEILING CONNECTION

CABLES TO CEILING











| SPECIFICATION CODE Example: 2 QTY LA2-ESS-TWO-22D-4H-WZ-830CK-STD-BPC-BK | | | | | | | | | | | | | | |
|--|--------------|--|-----|------|-----------|--------------|----------|----------------|-------|---------------------|-----|--|--|--|
| | LA2-ESS-TWO | | | | | | | | | | | | | |
| | QTY. | L33 1WU - | 0 | 2 | 3 | 4 | ¯[5 | 6 0 | | | | | | |
| 0 | | dan I AO Farantinla Tura | | | | | | | | | | | | |
| | | der LA2 Essentials Two i choices; additional lead | | | | | ection a | nd enter in th | ie co | rresponding box abo | ve. | | | |
| | 0175 | | | | IEIOUE | | | | | | | | | |
| 0 | SIZE Nominal | | | 2 | IEIGHT No | ominai | | | | | | | | |
| | 22SQ | 22" SQ | | | 4H | 4" HE | | | | | | | | |
| | 30SQ | 30" SQ | | | 8H | 8" HE | | | | | | | | |
| | 48SQ | 48" SQ | | | 12H | 12" HE | IGHI | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| _ | MATERIAL | | | | | | | | | | | | | |
| 3 | WAILMAL | | | | | | | | | | | | | |
| | GO | GESSO | | CUST | CU | STOM DLOR | | | | | | | | |
| | □ NL | NATURAL | | | | LON | | | | | | | | |
| | CR | CINDER | | | | | | | | | | | | |
| | SO CB2 | SILKEN OYSTER CRANBERRY X2 | | | | | | | | | | | | |
| | ☐ VC | VITAMIN C | | | | | | | | | | | | |
| | WZ | WIZARD | | | | | | | | | | | | |
| | MCR | MIDCENTURY RC | SEW | OOD | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| 4 | LED CRI/CCT | | | | | | _ | | | | | | | |
| | 830CK | 80 CRI / 3000K | | | | | | | | | | | | |
| | 835CK | 80 CRI / 3500K | | | | | | | | | | | | |
| | | 80 CRI / 4000K | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| 6 | SUSPENSION | SPENSION 6 CANOPY COLOR | | | | | | | RD | | | | | |
| | STD | 12"-96" | | WPC | WHITE | | | WH | | WHITE | | | | |
| | EXT* | 12" – 240" | | BPC | BLACK | | | ВК | | BLACK | | | | |
| | SM | Surface Mount | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |





