Overview



## Specifications

Lightweight arcylic frames clad in 50% post-consumer SHADE

recycled Sola Felt.

LIGHTING Solid state LED system

120v-277v input 2700K - 4000K 80 / 90 CRI light source Medium 82W Large 116W

**HARDWARE** Removable TGIC-free powder coated metal lid and

PCV power cord. Canopy and dress plate mounts to standard junction box (junction box provided by others). 3/64" stainless steel cables to ceiling.

Power cord to canopy

DIMMING Dimming 0-10v

MOUNTING Fully adjustable stainless steel aircraft cable. Contact

LightArt for lengths over 20'.

CERTIFICATION

CSA approved to UL standards Declare label certified

Living Building Challenge compliant

Damp rated

WARRANTY 5 year warranty on all standard components.

LED system rated for operation in ambient

environments up to 25°C.

**STANDARDS** 6 week lead time

250+ 3 form material options

(contact LightArt for custom material pricing)

TGIC-free powder coat PVC-free power cord










## **ACOUSTIC DRUM**

## **SHAPES & DIMENSIONS**







## Part Number Specification

ACOUSTIC DRUM

SPE	SPECIFICATION CODE Example: 2 QTY ACC-SHPE-DRUM-22D-4H-WZ-830CK-STD-WPC-WH						
	ACC-S	SHPE-DRUM				_	
QT	<b>Ү</b> .		0 0	3	<b>4 6</b>	6	0
			each number, make one ad times and/or costs m		in the correspond	ding box a	bove.
maioc	nes modifica e	snoices, adamonaried	ad times dirayor costs in	ау арргу.			
1 SI	ZE		2 HEIGHT				
[	30D	30" Dia		12" HEIGHT			
	44D	44" Dia		24" HEIGHT 36" HEIGHT			
				48" HEIGHT			
<b>8</b>	IATERIAL						
	ЕВ	EBONY	☐ EM	EMERALD	SF		SAFFRON
	☐ NF ☐ CA	NIGHTFALL CAST	☐ AD ☐ DK	ADMIRAL DUSK	☐ JP		JASPER ARIES
	ML	MINERAL	STB	STEELBLUE			OCHRE
	STL	STEEL	☐ PT	PLATINUM	ми		MUSTARD
	☐ AR ☐ NI	ARMOR NICKEL	SLT	SILT DRIFTWOOD	C1		CITRINE
	ZN	ZINC	☐ DN	DUNE			
3	_ED CRI/CCT				_		
	827CK	80 CRI / 2700K	930CK	90 CRI / 3000K			
	830CK	80 CRI / 3000K	□ 935CK	90 CRI / 3500K			
	835CK	80 CRI / 3500K					
	840CK 927CK	80 CRI / 4000K 90 CRI / 2700K					
	SHSDENGION	ENSION 6 CANOPY COLOR 7 POWER CORD					
5	SUSPENSION		_ 6 CANOPY COLO	л. 	POWER	ייסטעט	
	STD	12" – 96"	WPC	WHITE	v		WHITE
	EXT*	24" – 240"	ВРС	BLACK		sK	BLACK

\*Indicates modified choices; additional lead times and/or costs may apply.





