



## Specifications

LIGHTING Solid state LED system. 120v-277v input; 2700K-4000K in CRI >80 or 90; 8W

HARDWARE TGIC-free powder coated backplate mounts to

standard junction box (provided by others) Canopy and dress plate mounts to standard

DIMMING Dimming 0-10v

CERTIFICATION CSA approved to UL standards

Damp rated. ADA Compliant.

WARRANTY 5 year warranty on all standard components.

LED system rated for operation in ambient

environments up to 25°C.

**STANDARDS** 

6 week lead time 250+ 3form material options TGIC-free powder coat PVC-free power cord










Fixture Options SCONCE

**SHAPES & DIMENSIONS** SHADE COLOR OPTIONS



12"W X 8"H X 4"D



TRANSLUCENT SUEDE

Due to manufacturing and construction process used to create the Essentials and Connected collection, Pattern+ and wood grains will not match at fixture seams. Lead times subject to change.

## CANOPY / DRESS PLATE FINISH OPTIONS

WHITE







3 LED CRI/CCT

827CK

830CK

835CK

840CK 927CK

80 CRI / 2700K

80 CRI / 3000K

80 CRI / 3500K 80 CRI / 4000K

90 CRI / 2700K

930CK

935CK

90 CRI / 3000K

90 CRI / 3500K

SPECIFICATION CODE Example: 2	QTY COL-ECO-SCN-8H-LIK-830CK-WPB
COL-ECO-SCN	
Complete form to order Zero fixture(s). For each num *Indicates modified choices; additional lead times an	ber, make one selection and enter in the corresponding box above. nd/or costs may apply.
1 SIZE 2	MATERIAL
<mark> 8H</mark> 8"H	LIN VP LIN Linea Ivory + Noir VP Veil Pure
	LIK Linea Ivory + Khaki  TS Translucent Suede Varia
	LI CUST* Custom Color

4 BACKPLATE COLOR

WPB

WHITE

\*Indicates modified choices; additional lead times and/or costs may apply.





