













Specifications

CONSTRUCTION	Sola Felt over metal frame. Simple plug-together wiring and mechanical connectors at luminaire junctions.	ELECTRICAL	Emergency Battery—Emergency output: 10 watts for 90 minutes. Maximum Mounting height: 16.5ft. Compatible with Signify Bodine sinusoidal output emergency lighting inverters. Signify Bodine inverters allow designated lighting fixtures to serve as code-compliant emergency lighting sources during failure of normal AC power. For additional information see link: http://www.bodine.com/products/inverter.html
END CAPS	Fixture body color-matched Sola Felt standard; wood end caps optional	DRIVERS	120-277V constant current, dimming driver standard. Can be wired dimming or non-dimming. 0-10v dimming input with a range of 1%-100%. Dim-to-Off standard. Driver can be accessed from the fixture. Power factor of > .95. Total Harmonic Distortion (THD) of < 20%.
SHADES	9mm thick Sola Felt is a PET material, manufactured with 50% post-consumer recycled content. Sola Felt is a LBC Red List Free labeled product, eligible for LEED, Living Building Challenge, and other green building certification credits.	CERTIFICATION	Luminaire is CSA listed conforming to UL Standard 1598 in the U.S. and CAN/CSA C22.2 No. 250.0 in Canada. In accordance with NEC Code 410.73 (G), this luminaire contains an internal driver disconnect. Damp Location Rated. All electronic components are RoHS compliant, and the mechanical components of the luminaire have been verified to meet RoHS Directive 2002/95/EC. UL listed.
MOUNTING	Adjustable stainless steel aircraft cable, contact studio for lengths over 20'.	WARRANTY	5 year warranty on all standard components.
LUMEN MAINTENANCE	Reported TM-21 Lifetimes L90: >52,600 hours L80: >102,000 hours L70: >102,000 hours	CARE	The best way to remove airborne debris and dust from shades is to periodically vacuum. A Swiffer sheet or feathered duster can also be used for light dusting. To treat liquid stains, remove spills immediately with a clean damp cotton cloth or with detergent soap and warm water. Carpet and fabric cleaners can usually be used. Always test an inconspicuous area before applying cleaners to the actual stain.
DIFFUSION	Indirect Lighting: Snap-in diffuser with split diffusion optics creating a batwing optical distribution. Provides uniform distribution of light with a reduction in center beam intensity. Direct Lighting: Micro-structure diffusion materials providing glare control.		 
LIGHTING	Integrated LED light source offering high lumen output and efficacy. Color consistency of 3 SDCM. See additional information summarizing lumen distribution, wattage, and efficacy on following pages.		

DIMENSIONS Also available unlit. See Stratta Unlit Spec Sheet.



FELT COLOR OPTIONS




END CAP CONFIGURATIONS




CEILING CONNECTION

ULTRA SHALLOW CANOPY



CANOPY / DRESS PLATE FINISH OPTIONS



Declare.

Sola Felt, Clario, Hush Clad, and Tetria Acoustic Solutions 3form

Final Assembly: Salt Lake City, Utah, USA
 Life Expectancy: 20 Years
 End of Life Options: Salvageable/Recyclable in its Entirety, Take Back Program (Optional, Salt Lake City, Utah)
 EU CoC Screened: Does Not Contain

Ingredients:
 polyethylene terephthalate; 3-hydroxyphenylphosphorylpropanoic acid; Titanium dioxide; Carbon black; Spinning Finish

Living Building Challenge Criteria: Compliant

1-13 Red List: 0
 1-13 Red List Free: 13 Declared, 100% of 100ppm
 1-13 Red List Approved: VOC Content: Not Applicable
 1-13 Declared: 0

1-13 Material Performance: C294 Standard Method v13-2010
 1-14 Responsible Sourcing: Not Applicable

TFM-0003
 EXPIRES: 31 OCT 2022
 SCREENED: 21 SEP 2021
 Original Issue Date: 2019

INTERNATIONAL LIVING FUTURE INSTITUTE® livingfuture.org/declare



SABINS PER FIXTURE Equivalent square feet of perfect absorption

CENTER FREQUENCY (HZ)	49-16-2 STRATTA	49-12-2 STRATTA	49-6-2 STRATTA
100	0.66	0.24	-0.02
125	1.26	0.59	0.34
160	1.90	1.13	0.26
200	2.35	1.81	0.62
250	3.10	2.25	0.94
315	4.66	3.19	1.35
400	5.68	3.77	1.60
500	6.56	4.80	2.12
630	7.71	5.42	2.58
800	8.89	6.48	3.30
1000	10.01	7.33	3.61
1250	10.63	8.25	4.21
1600	11.36	8.65	4.58
2000	11.64	9.08	5.00
2500	11.82	9.26	5.09
3150	11.63	9.07	5.13
4000	11.50	8.96	5.16
5000	11.71	9.03	5.11
6300	11.93	8.99	5.25
8000	12.14	8.91	5.13
10000	12.03	8.99	5.24
AVERAGE OF 250, 500, 1000, 2000	7.83	5.86	2.92
EQUIVALENT SQ FT OF ACT (NRC 0.70)	11.18	8.38	4.17


The NRC of Stratta ranges from 0.75 to 1.00, depending on the size and configuration tested. Formal testing reports are available for more information.

Absorption

The Stratta line was tested in accredited laboratories to study the impact of fixture size and configuration on acoustic performance.


The acoustic testing of Stratta was conducted at NVLAP accredited laboratories and meets ISO 354 and ASTM C423. Formal test reports are available upon request.

- 49-16-2 ACOUSTIC STRATTA
- 49-12-2 ACOUSTIC STRATTA
- 49-6-2 ACOUSTIC STRATTA



LIGHT DISTRIBUTION OPTIONS

Consult factory or lightart.com for IES files, tested in accordance with IESNA LM79



PERFORMANCE

Based on 3500K / 80CRI / 80deg configuration

NOMINAL LUMEN OUTPUT (LM/FT)	INPUT POWER (W/FT)	EFFICACY (LM/W)
250	2.13	117
450	3.84	117
650	5.56	117
850	7.30	116
1050	9.05	116



SPECIFICATION CODE

Example: 2 QTY ACC-STR-BEAM-49L-12H-CT-FELT-CRW-CRLNA-STD-DRL-840CK-450LM-P01-SC-OS-WPC-WH

QTY. ACC-STR-BEAM - - - - - - - - - - - - - - -

1
2
3
4
5
6
7
8
9
10
11
12
13
14

Complete form to order Stratta fixture(s). For each number, make one selection and enter in the corresponding box above.

*Indicates modified choices; additional lead times and/or costs may apply.

1 LENGTH (Nominal)

- | | | | |
|------------------------------|--------------|-------------------------------|---|
| <input type="checkbox"/> 37L | 37.5" LENGTH | <input type="checkbox"/> 85L | 85.5" LENGTH |
| <input type="checkbox"/> 49L | 49.5" LENGTH | <input type="checkbox"/> 97L | 97.5" LENGTH |
| <input type="checkbox"/> 61L | 61.5" LENGTH | <input type="checkbox"/> CRL* | CUSTOM ROW LENGTH |
| <input type="checkbox"/> 73L | 73.5" LENGTH | | <small>Custom rows from 3' to 200'
in 1' increments available</small> |

2 HEIGHT (Nominal)

- | | |
|------------------------------|------------|
| <input type="checkbox"/> 6H | 6" HEIGHT |
| <input type="checkbox"/> 12H | 12" HEIGHT |
| <input type="checkbox"/> 16H | 16" HEIGHT |

3 FELT COLOR

- | | | | | | |
|------------------------------|-----------|------------------------------|-----------|------------------------------|---------|
| <input type="checkbox"/> EB | EBONY | <input type="checkbox"/> EM | EMERALD | <input type="checkbox"/> SF | SAFFRON |
| <input type="checkbox"/> NF | NIGHTFALL | <input type="checkbox"/> AD | ADMIRAL | <input type="checkbox"/> JP | JASPER |
| <input type="checkbox"/> CA | CAST | <input type="checkbox"/> DK | DUSK | <input type="checkbox"/> AS | ARIES |
| <input type="checkbox"/> ML | MINERAL | <input type="checkbox"/> STB | STEELBLUE | <input type="checkbox"/> OCH | OCHRE |
| <input type="checkbox"/> STL | STEEL | <input type="checkbox"/> PT | PLATINUM | <input type="checkbox"/> MU | MUSTARD |
| <input type="checkbox"/> AR | ARMOR | <input type="checkbox"/> SLT | SILT | <input type="checkbox"/> CT | CITRINE |
| <input type="checkbox"/> NI | NICKEL | <input type="checkbox"/> DW | DRIFTWOOD | | |
| <input type="checkbox"/> ZN | ZINC | <input type="checkbox"/> DN | DUNE | | |

4 ENDCAP Optional wood endcap

- | | |
|-------------------------------|---|
| <input type="checkbox"/> FELT | FELT BODY COLOR |
| | <small>Endcap will match shade material color</small> |
| <input type="checkbox"/> WOE* | OAK WOOD |
| <input type="checkbox"/> WAE* | ASH WOOD |

5 MOUNTING

- | | |
|-------------------------------|------------------------|
| <input type="checkbox"/> PM | INDIVIDUAL FIXTURE |
| <input type="checkbox"/> CRW* | CONTINUOUS ROW FIXTURE |

6 CONTINUOUS ROW LENGTH

- | | |
|---------------------------------|---|
| <input type="checkbox"/> CRLNA | NOT APPLICABLE |
| | <small>Individual lengths cannot be joined in the field</small> |
| <input type="checkbox"/> CUSRL* | CUSTOM ROW LENGTH |
| | <small>Specify custom length in 1' increments from 3' to 200'</small> |

ft

7 SUSPENSION

- | | |
|-------------------------------|------------|
| <input type="checkbox"/> STD | 12" - 96" |
| <input type="checkbox"/> EXT* | 24" - 240" |

8 FIXTURE DISTRIBUTION

- | | |
|------------------------------|--------------------------|
| <input type="checkbox"/> IRL | INDIRECT REGRESSED LIGHT |
| <input type="checkbox"/> DRL | DIRECT REGRESSED LIGHT |
| <input type="checkbox"/> IBW | INDIRECT BATWING |



INDIRECT DIRECT

CONTINUE TO NEXT PAGE TO COMPLETE SPECIFICATION

*Indicates modified choices; additional lead times and/or costs may apply.

CONTINUE SPECIFICATION

9 LED CRI / CCT

- 830CK 80 CRI / 3000K
- 835CK 80 CRI / 3500K
- 840CK 80 CRI / 4000K
- 927CK 90 CRI / 2700K
- 930CK 90 CRI / 3000K
- 935CK 90 CRI / 3500K

10 OUTPUT

- 250LM 250 LM/FT
- 450LM 450 LM/FT
- 650LM 650 LM/FT
- 850LM 850 LM/FT
- 1050LM 1050 LM/FT
- CU* CUSTOM
Specify custom value from 250 to 1050 lm/ft

_____ lm/ft

11 DIMMING AND CONTROLS

- P01 0-10V 1% DIMMING
- LEC* HI-LUME 1% ECOSYSTEM LED DRIVER
SOFT ON, FADE TO BLACK (LDE1 SERIES)
- EBM 0-10V 1% DIMMING
INTEGRATED EM BATTERY OPTION
*Max Lumen output limited — consult LightArt.
Available only for direct lighting option.*

12 CANOPY MOUNTING *5" Dia Canopy*

- JB JUNCTION BOX FEED/SUPPORT
- OS OFFSET JUNCTION BOX

13 CANOPY OPTIONS

- WPC WHITE
- BPC BLACK
- RWPC RECESSED WHITE
- RBPC RECESSED BLACK

14 POWER CORD

- WH WHITE
- BK BLACK

*Indicates modified choices; additional lead times and/or costs may apply.

