



# Casper Beams & Pendants

LightArt

# Pendant

Casper Pendants celebrate the simplicity of suspended light. Create a striking installation by clustering the pendants for an ultra modern look.



36"L×4"SQ (2), 72"L×2"SQ, 48"L×2"SQ PENDANTS IN RGB WHITE

# Beam

High-performance, low-glare lighting delivers soft and even illumination for extraordinary results.



60"L x 4"SQ BEAM

# Configurability

Create wayfinding solutions and directional beacons with custom lighting configurations that run through corridors, take sharp turns, and zigzag along hallways, lobbies, reception, and office spaces.



## Collaborative Spaces



Easily identify breakout or common rooms with illumination that integrates and highlights the overall design.

## Scale, Wayfinding, Illumination

A modern application uses Casper Beams and Pendants to create a lighting solution that elevates the space and adds design interest.

Designed to adapt to scale with customizable configurations and shapes to create stunning focal points with seamless integration.










Extended linear run lengths, modular shapes, RGB and tuneable white light output take Casper to a whole new level.



## Standards

LIGHTING	Integrated LED light source offering high lumen output and efficacy. Color consistency of 3 SDCM. See additional information summarizing lumen distribution, wattage, and efficacy on following pages. Tunable white and RGB options available.	CERTIFICATION	Luminaire is CSA listed conforming to UL Standard 1598 in the U.S. and CAN/CSA C22.2 No. 250.0 in Canada. In accordance with NEC Code 410.73 (G), this luminaire contains an internal driver disconnect. Damp Location Rated. All electronic components are RoHS compliant, and the mechanical components of the luminaire have been verified to meet RoHS Directive 2002/95/EC.
DIFFUSION	Frosted optical diffuser produces even illumination.	WARRANTY	5 year warranty on all standard components.
MOUNTING	Adjustable stainless steel aircraft cable, contact studio for lengths over 20'		














## Dimensions

PROFILES	LENGTHS
	
4" SQ	24" L
	
2.25" SQ	36" L
	
	48" L
	
	60" L
	
	72" L
	
	84" L
	
	96" L

## Alternative Output Options

RGB	Utilizes red, green, and blue (RGB) light to create a wide range of colors and hues	TUNABLE WHITE	Capability to change light temperature from warm to neutral (2700K–4000K)
			
			

## Beam Options

JOINTS	CUSTOM CONFIGURATIONS
	
90°	CLOSED SHAPE
	
108°	OPEN SHAPE
	
120°	MULTI-ANGLE RUN
	
135°	L-SHAPE
	
CREATES RECTANGLE	MULTI-LENGTH RUN
	
CREATES PENTAGON	
	
CREATES HEXAGON	
	
CREATES OCTAGON	