



CYLINDER & TUCK PENDANT

LIMITLESS VERSATILITY

LightArt®



Cylinder



Tuck

CYLINDER & TUCK PENDANT

*Two new pendant styles expand
LightArt's collection of versatile,
everyday fixtures.*

*Inspired by simplicity, these easy
to specify, customize, and adaptable
pendants are made for environments
and spaces in need of durable, beautiful,
and dependable lighting.*



CYLINDER PENDANT

*Elegant & Practical Light
Limitless Versatility*



CYLINDER PENDANT

FEATURES

- *Constructed from 3form Varia*
- *An inner and outer shade connected*
- *Two style options*
- *Available in 12”h, 18”h, and 24”h*
- *Five stock colors*
- *Integrated LED lighting*
- *Compatible dimming*
- *PoE compatible*





TUCK PENDANT

*Inspiring & Minimalist Light
Classic Simplicity*




TUCK PENDANT

FEATURES

- *Cost effective solution*
- *Constructed with 3form Varia*
- *One piece of material*
- *Three stock colors*
- *Integrated LED lighting*
- *Compatible dimming*
- *PoE compatible*



CYLINDER PENDANT




STYLE A
6.5"Dia x 12"H



STYLE A
6.5"Dia x 18"H



STYLE B
6.5"Dia x 24"H



STYLE B
6.5"Dia x 12"H



STYLE B
6.5"Dia x 18"H



STYLE B
6.5"Dia x 24"H

MATERIALS



Veil Pure



Linea Ivory
+ Noir



Linea Ivory



Linea Ivory
+ Khaki



Translucent
Suede

SPECIFICATIONS

LIGHTING:

LED module with single light emitting source, thermally managed to provide optimal performance. Specifiable in 2700K–4000K in CRI >80 or CRI >90, color accuracy within 3 SDCM. Also available in dim-to-warm.

PoE or PoE+ compatible (depending on required output): Integrates with Power over Ethernet lighting systems through standard, low voltage wires. See wattage table on page 4 for PoE or PoE+ compatibility.

Beam spreads from 28 degree narrow flood to 44 degree wide flood available, achieved with optics that are easily changed in the field.

E26 lamp model also available. Source lumens 800, delivered lumens approx 619, 90 CRI, nominal lifetime 15,000 hours.

CERTIFICATIONS:

CSA certified to CSA C22.2 No. 250.0, and conforms to UL standard 1598.

PoE Compatible fixtures meet UL 2108.

WARRANTY:


5 year warranty on all standard components. LED system rated for operation in ambient temperatures up to 25°C.

Suitable for Dry or Damp locations. Indoor use only.

LEAD TIME:

6 week lead time

TUCK PENDANT



ONE SIZE
6.5"Dia x 12"H

MATERIALS



Hush Gesso



Hush Natural



Hush Cinder

SPECIFICATIONS

LIGHTING:

LED module with single light emitting source, thermally managed to provide optimal performance. Specifiable in 2700K–4000K in CRI >80 or CRI >90, color accuracy within 3 SDCM. Also available in dim-to-warm.

Beam spreads from 30 degree narrow flood to 78 degree wide flood available, achieved with optics that are easily changed in the field.

CERTIFICATIONS:

CSA certified to CSA C22.2 No. 250.0, and conforms to UL standard 1598. CSA certified to UL 2108 for low-voltage systems.

WARRANTY:

5 year warranty on all standard components. LED system rated for operation in ambient temperatures up to 25°C.

Suitable for Dry or Damp locations. Indoor use only.

LEAD TIME:

6 week lead time

(206) 524-2223
INFO@LIGHTART.COM
WWW.LIGHTART.COM

LightArt®

Feb 2022 / MARCOM – Coil & Tuck Pendant / Rev 001

LIGHTART is a registered trademark of 3form, LLC. The products depicted herein may be covered by one or more of the following U.S. or international patents, and/or one or more U.S. or international patents pending: D604,890, D620,636, D665,120, D686,363, D745,206, 5,643,666, 5,894,048, 5,958,539, 5,998,028, and 6,025,069. For more information, see: http://www.3-form.com/downloads/3form_IP.pdf