

Brute Antenna



Industrial grade, low profile, ultra-wideband 4G/5G cellular antenna with both primary and diversity leads (MIMO) in a single base. Rated for outdoor use and designed to be vandal proof. Easy to install with either a direct (threaded stud) mount where there is a hole in the cabinet so that a locknut can be tightened down on the backside, or an incredibly strong magnetic mount that can be used on any ferromagnetic (iron or steel) metal surfaces.

Ideal when vandal resistance is important and for mounting in outdoor settings.



OC-1052 (Direct/Screw Mount)

OC-1053 (Magnetic Mount)

Part Number	Mount Type
OC-1052	Direct/Screw Mount with locknut
OC-1053	Magnetic Mount

Specifications


Dimensions	7.97" X 3.48" X 1.77"
Weight	2.5 lbs

Applications

ATMs, Digital Signs, Kiosk, Vending Machine, Gaming Equipment, Access Controls

Brute Antenna Technical Specifications

Cellular Specifications	
Frequency	617 - 960 MHz, 1710 - 6000MHz
Nominal Impedance	50Ω
VSWR	<2:8:1 @ 698 - 894 MHz <2:8:1 @ 1710 - 2700MHz
Radiation Pattern	Omni
Average Gain	3.3 dBi @ 617 -960 MHz 5.2 dBi @ 1710-6000MHz
Isolation	<-10 dB @ 617 -960 MHz <-10 dB @ 1710-6000MHz
Polarization	Vertical
Environmental Specifications	
Operating Temperature	-40 ~ +85° C
Storage Temperature	-40 ~ +85° C
RoHS Compliant	Yes
Ingress Protection Rating	IP67 Weatherproof Rated



Need more information?

Call our connectivity experts at 1-877-678-3343