











OptConnect Device Comparison

Product Name	Ideal Applications	Carriers	Dual Carrier	Type	Speed (megabits per second down/up)	Size	# of Ethernet Ports	Features & Benefits
4499 	Dial-up ATMs	verizon✓	No	4G LTE Cat 1 Router	1-6 / 1-3	203.2 x 116.9 x 33.1 mm	1	Protocol conversion, TID capture
4100 	ATMs, POS, and some Kiosks	verizon✓ AT&T	No	4G LTE Cat 1 Router	1-6 / 1-3	4.3 x 3.7 x 1 in 109 x 94 x 25 mm	2	Built for lower data consuming devices, Can run multiple devices at a time, Same heating temperature as the 4500
4500 	Smart Vending, Gaming Terminals, Digital Signage	verizon✓	No	4G LTE Cat 3 Router	8-20 / 2-6	4.5 x 3.75 x 1.125 in	2	Turn Key solution, PCI compliant, Lifetime warranty, Remote power cycle available
neo 	ATMs, POS, Digital Signage, Kiosks	verizon✓ AT&T	No	4G LTE Cat 3 Router	8-20 / 2-6	2.7 x 2.2 x 0.7 in	1	Plug n Play, Lightweight, rugged aircraft grade aluminum, Modular antennas, Wide coverage
mylo 	ATMs, POS, Sensor Applications	verizon✓ AT&T	Yes	4G/5G Cat M1	100 - 400 kilobits/s)	79.8 x 79.8 x 19.7 mm	1	Dual carrier, 4G/5G, Best congestion performance, Multi-carrier redundancy, Ideal for low speed and low data applications.

Product Name		Ideal Applications	Carriers	Dual Carrier	Type	Speed (megabits per second down/up)	Size	# of Ethernet Ports	Features & Benefits
solo		ATM, POS, Kiosk	verizon✓	No	4G LTE Cat 1 Router	1-6 / 1-3	79.8 x 79.8 x 19.7 mm	1	Compact, Light-weight, easy to install, Magnetic feet built in, Cost effective
ema		Customers looking to embed wireless connectivity into their device	verizon✓ AT&T	Yes	LTE Cat 4 Modem	10-30 / 2-10	29 x 33.78 x 10.67 mm 1.14 x 1.33 x 0.42 in	0	Small form factor, Robust 20 pin interface, automatic connection management and monitoring, Remote diagnostics
Accessories/Dev Kits									
ema:Play		Sandbox for customers to test ema			Development Kit		82.55 x 84.55 mm 3.25 x 3.33 in		Onboard Microcontroller Unit (MCU), Voltage monitors, Built in sensors and feedback, Efficient design
ema mPCIe		Can be used to add smart managed cellular connectivity to any device that has an available mPCIe slot, without the cost and delay of obtaining additional certifications			Adaptor		ema not inserted: 30 x 50.95 x 7.7 mm ema inserted: 30 x 50.95 x 12.3 mm		Compatible with OptConnect ema™ modems, Power and Status LED indicators, Eliminate the need for custom hardware designs to integrate an OptConnect ema™ modem
OptReboot		Can pair with any OptConnect unit			Remote Power Switch				Quick installation, Reboot anytime/anywhere, Cost-effective