

(N) ROOF ANCHOR DETAIL

48" MIN. WIDTH


FIELD VERIFY LOCATION OF ALL JOISTS AND BLOCKING.


EXISTING 1/2" PLYWOOD SHEATHING NOT SHOWN FOR CLARITY.

3" O.C. AT JOISTS

ROOF ANCHOR REFINFORCEMENT NOTES:

AT PERIMETER, AND 8" O.C.IN FIELD.





(E) TJI JOISTS AT 24" O.C.

-(N) 3/4" CDX PLYWOOD

FASTEN AT 6" O.C.

FASTEN AT 3" O.C.

ALONG TJI JOISTS

-8" O.C. AT FIELD

1 1/2"


AT PERIMETER




MINIST

6 A5.3


(N) HORIZONTAL LIFELINE DETAILS







FASTENERS SHALL BE COMPLETELY PENETRATE AND EMBED THROUGH REINFORCEMENT CDX AND EXISTING 1/2" SHEATHING. INSTALL (N) ROOF ANCHORS TO 3/4" CDX PLYWOOD BACKING PER MANUFACTURERS INSTRUCTIONS, #14 SCREWS MIN. (N) ROOF ANCHOR REINFORCEMENT

(N) PIPE VENT AT MTL. ROOF




(E) DISCONNECT SWITCH





(N) D.S. BRACKET AT PLASTER



(E) GUY WIRE WALL ANCHORS



(N) BIRD DETERRENT BRACKET

