

## D115SONB BOX PC [Preliminary]

- Applies to NVIDIA® Jetson Orin™ Nano series
- Support Super Mode
- For Smart Traffic, Smart Security and Smart City Applications

### Overview

AVerMedia's AI Box PC D115SONB equips powerful NVIDIA® Jetson Orin™ Nano super/Orin™ Nano normal modules. This efficient system-on-module (SoM) opens new worlds of embedded IoT applications with full analytic capabilities.

D115SONB is designed for the industry applications with spatial concern and feature a rich assortment of I/O ports for rapid AI-based solution development and seamless deployment as required by demanding business applications.

AVerMedia supports businesses of all sizes and offers customizable BSP services, flexible MOQ, in addition to NVIDIA's JetPack™ SDK.

### Enterprise-Leading Features

- Embedded NVIDIA® Jetson Orin™ Nano
- Supports super mode
- 2 x M.2. for WIFI and SSD
- 2 x GbE RJ-45 (Optional: Ethernet 1 supports PoE ; Ethernet 2 can be used for OOB management via NC-SI)
- OOB for Power cycling and Cloud serial console (Optional)
- 1 x 5G daughter board for 4G/5G card functions (Optional)
- 1 x HDMI output
- 20-pin expansion header
- Dimension: W: 190mm x L: 175mm x H:80mm (TBD)

### The AVerMedia Advantage



**Video Processing Technology**



**Flexibility & Reliability**



**Dedicated After-Sales Support**

AVerMedia understands that each business has a unique set of requirements that requires professional expertise and support. With AVerMedia, you are guaranteed to work with a proven global leader in video processing technology (200+ video capturing & streaming patents) with decades of experience processing multiple video signals for countless award-winning products.

A global leader that supports businesses of all sizes with comprehensive customization services (i.e., HW/PCB/BSP/etc.), flexible MOQ while ensuring a high-quality design and stable product. And for projects requiring additional security, we can provide customizable encryption hardware to support your privacy needs.

By partnering with us, a dedicated NVIDIA® ELITE Partner, our support-driven team offers prompt after-sales support so that your company stays focused on what matters most, customer acquisition.

## Specifications

Model	D115SONB-8G
Type	Box PC
NVIDIA Module Compatibility	NVIDIA® Jetson Orin™ Nano super/Orin™ Nano normal modules
Networking	2x GbE RJ-45 (Optional: Ethernet 1 supports PoE* ; Ethernet 2 can be used for OOB management via NC-SI**) 1xM.2. key E 2230 for wifi
Display Output	1 x HDMI output 3840 x 2160 at 30Hz for Orin Nano
Temperature	Operating temperature -25°C~60°C (for Orin Nano normal mode/Orin Nano super mode) Storage temperature -40°C ~ 85°C Relative humidity 40°C @ 95%, Non-Condensing
MIPI Camera Inputs (Internal)	2x 4 lane MIPI CSI-2, 22-pin FPC 0.5mm Pitch Connector
USB	1x USB 2.0 type C for recovery 2x USB 3.2 Type-A (Native 10Gbps per port)
Storage	1x M.2. key M 2280 for NVMe (256G SSD installed in box PC)
Expansion Header	20-pin: 2x I2C, 2x UART, 4x GPIOs, 1x CAN (EU terminal block)*** 15-pin & 10-pin: Supports OOB management via OOB module (optional, sold separately) 40-pin wafer: Supports 4G/5G card functions via daughter board (optional, sold separately)
Security	TPM 2.0 supported
Power requirement	DC in JACK on board & ATX 4-pin 12V/5A, 12V~24V is recommended.
Power Cord	US/JP/EU/UK/TW/AU/CN
Thermal Solution	Fanless solution
Buttons	Power and Recovery
RTC Battery	Support RTC battery and Battery Life Monitoring by MCU
Dimension	190mm (W) x 200mm (L) x 80mm (H) (TBD); Weight: 2kg (TBD)
Certifications	CE, FCC, VCCI, KC
Package	1x D115SON Box PC (256G SSD installed) 1x Adapter and Power cable

\* For details, please refer to the ["Accessory-PoE Board"](#) webpage.

\*\* For details, please refer to the ["Accessory-OOB module"](#) webpage. Ethernet 2 supports NC-SI for enabling Allxon OOB and In-Band functions simultaneously.

\*\*\*When equipped with the OOB module, 2x UART will be unavailable.



\*All specifications are subject to change without prior notice.

Optional Accessories

MIPI Camera	For 22-pin MIPI connector: 1. Raspberry pi imx219 & imx477 (V2) 2. Manufacturer: APPRO.PHO <ul style="list-style-type: none"><li>B-04: IMX179 (8M) MIPI, 1080P (30fps)</li></ul>
-------------	--

Ordering Information

Model	SKU Number	NVIDIA SOM	SSD	POE function (PSE)	OOB Module	Mechanical Info and weight
D115SONB	D115SONB-8G-001	Orin Nano 8G	256G	-	-	<ul style="list-style-type: none"><li>W: 190mm x L: 175mm x H: 80mm (TBD)</li><li>Weight: 2kg (TBD)</li></ul>

\*With the optional OOB module, the default configuration uses Ethernet 2 on the D115W for OOB management, rendering the OOB-Ethernet on the OOB module inactive. Alternatively, we offer another option that allows users to manage via the Ethernet on the OOB module, changing the box PC configuration from 2 RJ45 ports to a total of 3 RJ45 ports, including the RJ45 on the OOB module.



\*All specifications are subject to change without prior notice.