

D115WONB-1 Box PC

NVIDIA® Jetson Orin™ Nano module

For Smart Retail, Smart Security and Smart City Applications



Overview

AVerMedia's AI Box PC D115WONB-1 equips powerful NVIDIA® Jetson Orin™ Nano module. This efficient system-on-module (SoM) opens new worlds of embedded IoT applications with full analytic capabilities.

D115WONB-1 is designed for the industry applications with spatial concern and feature a rich assortment of I/O ports for rapid AI-based solution development and seamless deployment as required by demanding business applications.

AVerMedia supports businesses of all sizes and offers customizable BSP services, flexible MoQ, in addition to NVIDIA's JetPack™ SDK.

Enterprise-Leading Features

- Embedded NVIDIA® Jetson Orin™ Nano
- 2 x M.2. for WIFI and SSD
- 2 x GbE RJ-45 (Optional: Ethernet 1 supports PoE ; Ethernet 2 can be used for OOB management via NC-SI)
- OOB for Power cycling and Cloud serial console (Optional)
- 1 x 5G daughter board for 4G/5G card functions (Optional)
- 1 x HDMI output
- 20-pin expansion header
- Operating temperature -25°C~60°C
- Dimension: W: 126mm x L: 96mm x H: 74mm
- Support Allxon 24/7 Edge AI device remote management with OOB disaster recovery solutions



The AVerMedia Advantage



Video Processing Technology



Flexibility & Reliability



Dedicated After-Sales Support

AVerMedia understands that each business has a unique set of requirements that requires professional expertise and support. With AVerMedia, you are guaranteed to work with a proven global leader in video processing technology (200+ video capturing & streaming patents) with decades of experience processing multiple video signals for countless award-winning products.

A global leader that supports businesses of all sizes with comprehensive customization services (i.e., HW/PCB/BSP/etc.), flexible MoQ while ensuring a high-quality design and stable product. And for projects requiring additional security, we can provide customizable encryption hardware to support your privacy needs.

By partnering with us, a dedicated NVIDIA® ELITE Partner, our support-driven team offers prompt after-sales support so that your company stays focused on what matters most, customer acquisition.

Specifications

Model	D115WONB-1
Type	Box PC
NVIDIA Module Compatibility	NVIDIA® Jetson Orin™ Nano 8G module
Networking	<ul style="list-style-type: none"> 2x GbE RJ-45 Optional: Ethernet 1 supports PoE* ; Ethernet 2 can be used for OOB management via NC-SI** 1xM.2. key E 2230 for wifi
Display Output	1 x HDMI output3840 x 2160 at 30Hz for Orin Nano
Temperature	Operating temperature -25°C~60°C Storage temperature -40°C ~ 85°C Relative humidity 40 °C @ 95%, Non-Condensing
MIPI Camera Inputs (Internal)	2x 4 lane MIPI CSI-2, 22-pin FPC 0.5mm Pitch Connector
USB	1x USB 2.0 type C for recovery 2x USB 3.2 Type-A
Storage	1x M.2. key M 2280 for NVMe (256G SSD installed in box PC)
Expansion Header	<ul style="list-style-type: none"> 20-pin: 2x I2C, 2x UART, 4x GPIOs, 1x CAN (EU terminal block)*** 10 pins x2: support OOB module (optional, sold separately) 5-pin & 30-pin wafer: Supports 4G/5G card functions via daughter board (optional, sold separately)
Power requirement	DC in JACK on board & ATX 4-pin 12V/5A, 9V~24V is recommended.
Power Cord	US/JP/EU/UK/TW/AU/CN
Thermal Solution	Fanless solution
Buttons	Power and Recovery
RTC Battery	Support RTC battery and Battery Life Monitoring by MCU
PCB/Electronics Mechanical Info	<ul style="list-style-type: none"> W: 126mm x L: 96mm x H: 74mm Weight: 1kg
Certifications	CE, FCC, KC
Package	1x Box PC (256G SSD installed) 1x Adapter and Power cable

* For details, please refer to the ["Accessory-PoE Board"](#) webpage.

** For details, please refer to the ["Accessory-OOB module"](#) webpage. Ethernet 2 supports NC-SI for enabling Allxon OOB and In-Band functions simultaneously.

***When equipped with the OOB module, 2x UART will be unavailable.



*All specifications are subject to change without prior notice.

Optional Accessories

MIPI Camera	For 22-pin MIPI connector: 1. Raspberry pi imx219 & imx477 (V2) 2. Manufacturer: APPRO.PHO <ul style="list-style-type: none">B-04: IMX179 (8M) MIPI, 1080P (30fps)
-------------	--

Ordering Information

Model	SKU Number	NVIDIA SOM	SSD	POE function (PSE)	OOB Module	Mechanical Info and weight
D115WONB-1	D115WONB-8G-0013	Orin Nano 8G	256G	-	4G module	<ul style="list-style-type: none">W: 126mm x L: 96mm x H: 74mmWeight: 1.1kg

*With the optional OOB module, the default configuration uses Ethernet 2 on the D115W for OOB management, rendering the OOB-Ethernet on the OOB module inactive. Alternatively, we offer another option that allows users to manage via the Ethernet on the OOB module, changing the box PC configuration from 2 RJ45 ports to a total of 3 RJ45 ports, including the RJ45 on the OOB module.



*All specifications are subject to change without prior notice.