

D133ONB-1 Box PC

NVIDIA® Jetson Orin™ Nano module

For Smart Traffic, Smart Security and Smart City Applications



Overview

AVerMedia's D133ONB-1 Box PC equips powerful NVIDIA® Jetson Orin™ Nano modules. This efficient system-on-module (SoM) opens new worlds of embedded IoT applications with full analytic capabilities

D133ONB-1 Box PC is designed for the industry applications with spatial concern and compact yet efficient for rapid AI-based solution development and seamless deployment as required by demanding business applications.

AVerMedia supports businesses of all sizes and offers customizable BSP services, flexible MoQ, in addition to NVIDIA's JetPack™ SDK.

Enterprise-Leading Features

- Equips NVIDIA® Jetson Orin™ Nano module
- 2 x GbE RJ-45 (Optional: Ethernet 2 can be used with OOB for RMII function)
- 1 x OOB for Power cycling and Cloud serial console (Optional)
- 1 x 5G daughter board for 4G/5G functions (Optional)
- 2 x USB 3.2 & 1 x HDMI output
- 2 x M.2 key for SSD/wifi
- 20-pin expansion header
- Operating temperature: -25°C ~ 60°C
- Support Allxon 24/7 Edge AI device remote management with OOB disaster recovery solutions



The AVerMedia Advantage



Video Processing Technology



Flexibility & Reliability



Dedicated After-Sales Support

AVerMedia understands that each business has a unique set of requirements that requires professional expertise and support. With AVerMedia, you are guaranteed to work with a proven global leader in video processing technology (200+ video capturing & streaming patents) with decades of experience processing multiple video signals for countless award-winning products.

A global leader that supports businesses of all sizes with comprehensive customization services (i.e., HW/PCB/BSP/etc.), flexible MoQ while ensuring a high-quality design and stable product. And for projects requiring additional security, we can provide customizable encryption hardware to support your privacy needs.

By partnering with us, a dedicated NVIDIA® ELITE Partner, our support-driven team offers prompt after-sales support so that your company stays focused on what matters most, customer acquisition.

Specifications

Model	D133ONB-1
Type	Box PC
NVIDIA Module Compatibility	NVIDIA® Jetson Orin™ Nano 8G
Networking	1 x GbE RJ-45 1 x M.2. key E 2230 for wifi
Display Output	1 x HDMI output 3840 x 2160 at 30Hz for Orin Nano
Temperature	Operating temperature -25°C~60°C Storage temperature -40°C ~ 85°C Relative humidity 40 °C @ 95%, Non-Condensing
MIPI Camera Inputs	2 x 4 lane MIPI CSI-2, 22 pin FPC 0.5mm Pitch
USB	1 x USB 2.0 type C for recovery 2 x USB 3.2 Type-A
Storage	1x M.2. key M 2280 for NVMe (256G SSD installed)
Expansion Header	20 pins: 2x I2C, 1x UART, 9x GPIOs 20 pins: 2x I2C, 1x UART, 9x GPIOs 15 pins: support OOB module (optional, sold separately)* 5 pins & 30 pins: support 4G/5G functions via daughter board (optional, sold separately)*
Power consumption	14.4W to 25.4W
Input Power	3.5mm Screw Terminal; 12V/5A, 9V~24V is recommended.
Power Cord	US/JP/EU/UK/TW/AU/CN
Thermal solution	Fan solution
Buttons	Power and Recovery
RTC Battery	Support RTC battery and Battery Life Monitoring by MCU
Dimension/Weight	W: 93mm x L: 81.2mm x H: 74.4mm Weight: 500g
Certifications	CE, FCC, KC
Package	1x Box PC 12V power adapter/Power cord

*For more detailed specification of OOB module, please check the "Accessory" page.

**If paired with the OOB Module/5G/frame grabber, then the inside USB is not available.

***All specifications are subject to change without prior notice.




*All specifications are subject to change without prior notice.

Optional Accessories

MIPI Camera	For 22pin MIPI connector: 1. Raspberry pi camera v2 /raspberry pi camera v3 2. Manufacturer: APPRO.PHO <ul style="list-style-type: none">B-04: IMX179 (8M) MIPI, 1080P (30fps)
-------------	--

Ordering Information

Model	SKU Number	NVIDIA SOM	SSD	OOB Module [Preliminary] 
D133ONB	D133ONB-8G-001	Orin Nano 8G	256G	-
D133ONB-1	D133ONB-8G-002	Orin Nano 8G	256G	RMII Function

*If paired with the OOB Module/5G/frame grabber, then the inside USB is not available.
**For more detailed specification of OOB module, please check the "Accessory" page.
***All specifications are subject to change without prior notice



*All specifications are subject to change without prior notice.